

Maßtabelle Rundlocher

Maximale Materialstärken für Stahl (St 37), Edelstahl (VA) und Aluminium

Art.-Nr.	Ø Loch	Gewinde		Zugbolzen	Max. Materialstärke in mm		
	mm	metrisch	PG	Ø mm	St 37	Edelstahl (VA)	Aluminium
014007	12,7	M 12	PG 7	9,5	2,0	1,0	3,0
014012	15,2	-	PG 9	9,5	2,0	1,0	3,0
014018	16,5	M 16	-	9,5	3,0	2,0	3,0
014018-11	16,5	M 16	-	11,1	3,0	3,0	4,0
014030	18,4	M 18	PG 11	9,5	3,0	2,0	3,0
014036	20,4	M 20	PG 13	9,5	3,0	2,0	3,0
014036-11	20,4	M 20	PG 13	11,1	3,0	3,0	4,0
014042	22,5	-	PG 16	9,5	3,0	2,0	3,0
014042-11	22,5	-	PG 16	11,1	3,0	3,0	4,0
014052	25,4	M 25	-	9,5	3,0	2,0	3,0
014052-11	25,4	M 25	-	11,1	3,0	3,0	4,0
014062	28,3	-	PG 21	9,5	3,0	2,0	3,0
014082	30,5	-	-	9,5	3,0	2,0	3,0
014085	32,5	M 32	-	19,0	3,0	3,0	4,0
014096	37,0	-	PG 29	19,0	3,0	3,0	4,0
014108	40,5	M 40	-	19,0	3,0	3,0	4,0
014120	43,2	-	-	19,0	3,0	3,0	4,0
014128	47,0	-	PG 36	19,0	3,0	3,0	4,0
014138	50,8	M 50	-	19,0	3,0	3,0	4,0
014146	54,0	-	PG 42	19,0	3,0	3,0	4,0
014154	60,0	-	PG 48	19,0	3,0	3,0	4,0
014160	63,5	M 63	-	19,0	3,0	3,0	4,0
010161	68,0	-	-	19,0	3,0	3,0	4,0
010165	70,0	-	-	19,0	3,0	3,0	4,0
014075	75,5	M 75	-	19,0	3,0	3,0	4,0
010169	76,2	-	-	19,0	3,0	3,0	4,0
010173	80,0	-	-	19,0	3,0	3,0	4,0
114082	82,0	-	-	19,0	3,0	2,0	4,0
010180	89,0	-	-	19,0	3,0	2,0	4,0
010182	92,0	-	-	19,0	3,0	2,0	4,0
010186	100,5	-	-	19,0	3,0	2,0	4,0
010194	115,5	-	-	19,0	3,0	2,0	4,0
010196	120,0	-	-	19,0	3,0	2,0	4,0

Gelb markiert: Ausführungen mit Zugbolzen Ø 11,1 mm – damit Edelstahl bis 3 mm auch bei kleinen Lochdurchmessern.

Nicht gelistete Abmessungen und Sonderformen nach Zeichnung fertigen wir auf Anfrage. Nennen Sie uns Lochmaß, Werkstoff und Materialstärke.